



Stokvis Trading B.V.
A SOLID PARTNER IN BUSINESS



Lubo International®
SMART LUBRICATION FOR PARTS

LUBO LUBRICATION

No greasy paste, No coldwelding

Applications

Lubo Lubricant can be applied to all stainless steel fasteners.
After application, the product will remain in a fixed, dry state.
Upon friction by fastening, the lubricant will melt and serve it's purpose.
Afterwards it will return to it's fixed state.

Main advantages Lubo lubricant

1. Significant savings in both cost and time.
 - Once treated, the product can be used instantly. No post-treatment or past required.
 - Items can be unscrewed or loosened at all times without difficulty.
 - Lubo Lubricant leaves it's fixed state only temporarily on the exact fastening spot, taking out the need for cleaning tools
2. The product's composition does not include bestial fats which limit life time.
3. Lubo Lubricant is completely FDA compliant

Product Features

- Prevents coldwelding
- Harmless to environment and people
- Efficient
- Low and constant friction coefficient
- Makes (dis)assembling easy
- Can be used in combination with all kind of fixing material
- Applicable from -120 C to +1400 C
- In accordance with ELV (2000/53/EG)
Free from Chrome, Cadmium, Nickel, Leas, Mercury & Molybdeen
- Complies with FDA 21 CFR 175.300 chapter (c) (4)

